
Brief Description:

CPV remote proportioning packages proportion virgin and regrind materials in conjunction with central vacuum receivers.

AV and SV sequencing valves are for sequencing vacuum and central vacuum conveying applications. All CPDB blowback pumps use SV style valves.

Standard Features:

- Proportioning valve assembly
- 2 aluminum pick-up wands
- Two (2) 10' vinyl flex hoses
- 4 hose clamps
- O-ring coupler
- Controller assembly with quick-connect cable assembly (specify voltage)
- Line sizes available: 1.5", 2.0", 2.5"

Optional Features

- Hopper-mount, wall-mount, or floor stand (CPV)
- Spare controller assembly (CPV)
- Consult factory for other sizes or voltages



CPV Remote Proportioning Valve

Available in 1.5", 2.0", or 2.5" OD inlet/outlet tubes.
Hopper-mount (HM), stand-mount (SM), or wall-mount (WM)

Voltage Configuration	Supply Voltage	Control Voltage
B24	115/1/50-60	24 VDC
B115	115/1/50-60	115/1/50-60
D24	230/1/50-60	230/1/50-60
D115	230/1/50-60	115/1/50-60
E24	24 VDC	24 VDC



AV/SV Air-Operated Sequencing Valves

Line Size in. dia. OD (mm)	Sequence T-Valve	Sequence Valve Plugs	Atmospheric Valve
1.5 (38.1)	SV1.5	SV1.5P	AV1.5
2 (50.8)	SV2	SV2	AV2
2.5 (63.5)	SV2.5	SV2.5P	AV2.5
3 (76.2)	SV3	SV3P	AV3
4 (101.6)	SV4	SV4P	AV4
4.5, 4" sch. 10 (114.3)	SV4.5	SV4.5P	AV4.5
5 (127)	SV5	SV5P	AV5



www.colortronicna.com

Corporate Headquarters:
Colortronic North America, Inc.
4100 Market Place
Flint, MI 48507
PH: 810-720-7300
FX: 810-720-2598
colortronicweb@corpemail.com

Dimensions and data not binding. Copyright by Colortronic 2004.