
MSM 2400 Series Central Granulators

Colortronic's MSM2400 Series is one of the most versatile central granulators available. Ideally suited for applications including large injection-molded parts, blow-molded parts, automotive moldings, light purgings, furniture and appliance parts, etc. The MSM2400 Series comes in 27" (700 mm), 39" (1000 mm), and 56" (1400 mm) widths, cutting circle diameter of 24", and horsepower options from 50 through 150 hp with throughput rates ranging from 1800 to 6000 lbs/hr.

Standard Features

- Unique rotor and disc design reduces frictional heat, helps prevent end plate smearing
- Exclusive Twinshear™ slicing action reduces energy consumption, fines and extends knife life
- Split chamber, easy cleanout service access

Low Heat Granulation

- Unique rotor and cutting chamber design helps prevent polymer "melt down"
- Virtually eliminates "end plate smearing"
- End ring (disc) rotates in relationship to the cutting chamber, vastly improving airflow and minimizing frictional heat

Reduced Energy Consumption

- Made possible by the Twinshear™ "scissor cutting" action knife design
- More efficient than chopping motion knife designs
- Uses lower horsepower motor without sacrificing throughput performance

Optional Features

- Multiple hopper designs
- Adjustable rotor knives
- Replaceable rotor knife seats



Specifications

Specifications	MSM2428	MSM2439	MSM2456
Throat Size	600 x 700 mm (24" x 28")	600 x 1000 mm (24" x 40")	600 x 1400 mm (24" x 56")
Cutting Circle	600 mm (23 5/8")		
Throughput (3/8" screen)	820 kg (1800 lbs.)	1200 kg (2500 lbs.)	1600 kg (3500 lbs.)
Infeed	Convey		
Cutting Chamber	(2) Bed Knife Chevron		
Rotor	(3) Knife Chevron		
Rotor Knives	(6) HCHC		
Bed Knives	(6) HCHC		
Screen Diameter	9.4 mm (3/8" dia.)		
Base	Plate Type		
Discharge	Airveyor		
Motor	37 kW (50 HP)	90 kW (100 HP)	90 kW (125 HP)
Drive	V-Belt		
Electrical Components	Safety switches wired into common junction box		
Controls	To suit voltage -110 V at operator station		
Labels	Labels and plates provided for operator safety		
Accessories	Conveyors, blowers, cyclone separators to suit application		
Feed Height	2175 mm (104 3/4")		
Length	2660 (104 3/4")		
Width	1473 mm (58")	1778 mm (70")	2184 mm (86")
Height	3429 mm (125")		
Weight	4545 kg (10,000 lbs.)	5910 kg (13,000 lbs.)	7270 kg (16,000 lbs.)

Easy Accessibility and Cleanout

- Due to split chamber design, which raises the upper half of the cutting chamber and lowers the screen cradle and discharge assembly via motorized screw jacks
- 50% reduction in cleanout time
- Simplifies access for knife adjustments and replacement
- Air evacuation piping system does not need to be disconnected



Heavy solid flywheel
for added inertia

Low Noise Operation

- Standard double-walled hopper helps avoid the need for sound insulation rooms on plant floor



Clam shell opening with
mechanical screw jack



Easy access for
maintenance and color
changes

www.colortronicna.com

Corporate Headquarters:

Colortronic North America, Inc.
4100 Market Place
Flint, MI 48507
PH: 810-720-7300
FX: 810-720-2598
colortronicweb@corpemail.com

Dimensions and data not binding. Copyright by Colortronic 2004.